

SPECIAL PACKAGING INSTRUCTIONForm Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, Va 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, D.C. 20503. Please do not return your form to either of these addresses.

1. PART OR DRAWING NO. NOMENCLATURE 11608342 CYLINDER ASSY			2. CODE IDENT 19200		3. SPI NO. (AM)P11608342	
4. NATIONAL STOCK NUMBER 3040005699554			5. DATE OF DRAWING/SPI 04/21/98		6. REVISION / ERR NO. -/L8K2007	
7. QUP 1/EA	8. ICQ	9. UNIT PACK WT. (LB) (0.0) 2.0	10. UNIT PACK CU (CU. FT) (0.000) 0.059		11. UNIT PACK SIZE (INCHES) (00.0) 8.5 X 4.0 X 3.0	
			18. STEPS	19. REQD	20. DESCRIPTION	
			1	AR	PRESERVATIVE, MIL-H-46170, SEE NOTE A CAPS/PLUGS, MIL-C-5501 WRAP, MIL-P-130, TYPE I, SEE NOTE B CONTAINER, ASTM D 5118, STYLE FOL, TY COR, GRADE 200, CLASS DOM CLOSURE, ASTM D 1974, METHOD 4B3 BAG, MIL-B-117, TYPE I, CLASS E CONTAINER, ASTM D 5118, STYLE FOL, TY COR, GRADE W5c, OR W6c, CLASS WR CLOSURE, ASTM D 1974, SEALING METHOD B	
			2	3		
12. MILITARY PRESERVATION MIL-STD-2073-1C, METHOD 42			3	AR		
			4	1		
13. CLEANING			5			
*			6	1		
14. DRYING			7	1		
			8			
15. PACKING						
a. LEVEL A MIL-STD-2073-1C						
b. LEVEL B MIL-STD-2073-1C						
16. MARKING MIL-STD-129						

17. NOTES / DRAWING

***UNLESS OTHERWISE SPECIFIED, CLEANING AND DRYING SHALL BE IN ACCORDANCE WITH PARAGRAPH 5.2.1 OF MIL-STD-2073-1C.**
WEIGHTS AND SIZES ARE ESTIMATED AND MAY VARY SLIGHTLY.
INTERMEDIATE PACKAGING AND PACKING WILL BE IN ACCORDANCE WITH SPECIFICATION MIL-STD-2073-1C OR AS OTHERWISE SPECIFIED HEREON.

A) USE PRESERVATIVE TO LUBRICATE INTERNAL PASSAGES AND THEN DRAIN TO DRIP POINT.

B) UTILIZE SUFFICIENT WRAP TO ENSURE A TIGHT PACK.

WSC: JH ITEM SIZE: **7.8 X 3.0 X 2.0**ITEM WEIGHT: **1.5**APPROVED: **JAMES F. ZOLL**

STATEMENT A, UNLIMITED

DOCUMENT SUMMARY LIST

Item: M60 Cylinder Assy
NSN: 3040-00-569-9554
Control Number/PRON: P48ANWX4

Identifies all first tier documents (cited in SOW) (applicable DIDs). Also included are all referenced documents (2nd, (includes DID block 10 references), 3rd and lower tier) which have been tailored.

DOCUMENT CATEGORY:

CATEGORY O - Unless otherwise specified in the solicitation, contract, or contract modifications, all documents are for guidance and information only.

CATEGORY 1 - The requirements contained in the directly cited document are contractually applicable to the extent specified. All referenced documents are for guidance and information only.

CATEGORY 2 - The requirements contained in the directly cited document and the reference documents identified in the directly cited document are contractually applicable to the extent specified. All subsequently referenced documents are for guidance and information only.

CATEGORY 3 - Unless otherwise specified in the solicitation, contract or contract modification, all requirements contained in the directly cited document and all reference and subsequently referenced documents are contractually applicable to the extent specified.

Document Number (Contract Reference) Applicable Tailoring	Document Title	Document Date/ Document Category
1. ANSI/ISO/ASQC Q9003 or equivalent	Quality Systems – Model for Quality Assurance in Final Inspection and Test	18 Jul 94
